

Attorney's Docket:  
99P7740US

PATENT APPLICATION  
09/378,108

2

### IN THE CLAIMS

1. (Currently Amended) A system for minimizing the loss of information in cordless communications, comprising:

a first data station having control logic, the control logic operable to:

establish a plurality of individual communication channels needed to transmit information between the first data station and a second data station, ~~each of the channels associated with a unique channel frequency;~~

select a first ~~unique~~ channel frequency to be used for the first channel between the two data stations;

measure one or more parameters for evaluating interference of the first channel during transmission;

determine based on the one or more measured parameters ~~interference of the first channel during transmission~~ a spectral separation between from the first channel and ~~at least one other channel;~~ and

select a unique channel frequency for ~~the~~ the at least one other channel based on the first channel and the determined spectral separation ~~of the at least one other channel;~~ and

response logic residing in the second data station, the response logic operable to receive the information from the first data station on the plurality of communication channels.

2. (Original) The system of Claim 1, wherein the channels are operable to both transmit and receive information in duplex.

3. (Previously Presented) The system of Claim 1, the interference measured by a bit error rate of the first channel.

4. (Previously Presented) The system of Claim 1, wherein the bit error rate comprises either a short-term error rate or a long-term error rate.

DAL01:786293.1

Attorney's Docket:  
99P7740US

PATENT APPLICATION  
09/378,108

3

5. (Original) The system of Claim 1, wherein each channel frequency is changed using a frequency hopping scheme.

6. (Original) The system of Claim 1, wherein the control logic is further operable to:

- a) model interference encountered over individual channels between the data stations; and
- b) select parameters that minimize the loss of information over each of the individual channels.

DAL01:786293.1

Attorney's Docket:  
99P7740US

PATENT APPLICATION  
09/378,108

4

7. (Currently Amended) A method for minimizing the loss of information in cordless communications, comprising:

a) establishing a plurality of individual communication channels between at least two data stations;

b) selecting a first ~~unique~~ carrier frequency to be used for ~~the~~ a first of the plurality of channels;

c) measuring one or more parameters for evaluating interference of the first carrier frequency during transmission:

d) ~~determining based on the one or more measured parameters interference of the first of the plurality of channel during transmission~~ a spectral separation between from the first carrier frequency of the plurality of channels ~~and at least one other channel~~ relating to achieving a maximum throughput of information over the channels between the data stations; and

~~d) e)~~ selecting a ~~unique~~ second carrier frequency for ~~the~~ at least one other channel based on the first ~~unique~~ carrier frequency and the determined spectral ~~separation of the at least one other of the plurality of channels.~~

8. (Original) The method of Claim 7, wherein the maximum throughput of information over the channels is equal to the maximum throughput of information over the plurality of channels.

9. (Previously Presented) The method of Claim 7, wherein the determining step further comprises measuring error rates for a plurality of frequencies usable for each of the channels.

DAL01:786293.1

Attorney's Docket:  
99P7740US

PATENT APPLICATION  
09/378,108

5

10. (Original) The method of Claim 7, wherein the determining step further comprises:

- a) modeling interference over one of the channels; and
- b) selecting parameters that minimize the loss of information over the plurality of channels.

11. (Previously Presented) The method of Claim 7, further comprising determining parameters relating to achieving a maximum throughput of information over the channels between the data stations at predetermined intervals of time.

12. (Previously Presented) The method of Claim 7, further comprising changing the frequency of each channel utilizing a frequency hopping scheme.

13. (Previously Presented) The method of Claim 12, wherein the selecting a unique frequency step comprises separating all of the frequencies at an optimal spectral separation.

14. (Previously Presented) The method of Claim 7, further comprising selecting the unique frequency of the at least one other channel from a table.

DAL01:786293.1

Attorney's Docket:  
99P7740US

PATENT APPLICATION  
09/378,108

6

15. (Currently Amended) A method for minimizing the loss of information in cordless communications, comprising:

- a) providing at least two data stations having a plurality of communication channels to transmit information between the data stations;
- b) determining a first ~~unique~~ carrier frequency for the a first of the channels between the data stations;
- c) measuring one or more parameters for evaluating interference of the first carrier frequency during transmission;
- d) determining based on the one or more measured parameters ~~interference~~ during transmission a spectral separation between from the first of the channels ~~and the next one of the channels;~~
- e) ~~d)~~ repeating the steps for another channel; and
- f) ~~e)~~ selecting ~~unique~~ carrier frequencies for all of the plurality of channels based on the determined spectral separations ~~separation between and~~ the first channel ~~and each of the remainder of the plurality of channels.~~

16. (Previously Presented) The method of Claim 15, wherein the determining a spectral separation step further comprises determining parameters to yield an optimal spectral separation.

17. (Original) The method of Claim 15, wherein the determining parameters step further comprises:

- a) evaluating whether any signal source is interfering with the channel between the data stations on the first unique carrier frequency; and
- b) selecting another carrier frequency for the channel.

18. (Previously Presented) The method of Claim ~~15~~ 16, wherein the parameters represent an error rate measured over the channel.

DAL01:786293.1

Attorney's Docket:  
99P7740US

PATENT APPLICATION  
09/378,108

7

19. (Original) The method of Claim 15, further comprising the data stations transmitting information that is time division multiplexed and time division duplexed over the communication channels.

20. (Previously presented) The method of Claim 15, wherein steps (b)-(e) are performed at regular intervals of time.

DAL01:786293.1

Attorney's Docket:  
99P7740US

PATENT APPLICATION  
09/378,108

8

21. (Currently Amended) An apparatus for minimizing the loss of information in cordless communications comprising control logic, the control logic operable to:

select a first ~~unique~~ channel frequency associated with one of a plurality of communication channels;

access a plurality of frequency sets, each frequency of a frequency set corresponding to a channel;

remove any poor quality frequency set from the plurality of frequency sets;

measure one or more parameters for evaluating interference of the first channel during transmission;

determine based on the one or more measured parameters ~~interference of at least one channel during transmission one or more parameters relating to~~ a spectral separation from the first channel frequency between at least two of the channels, the spectral separation describing a separation between a pair of unique channel frequencies associated with the channels; and

select at least one ~~unique~~ channel frequency for the remainder of the plurality of channels based on the ~~related~~ determined spectral separation and selected from at least one of the plurality of frequency sets.

22. (Cancelled)

DAL01:786293.1